Ⓐ

ASSEMBLY INSTRUCTION

SKU# 512-983

NOTE: Please consult a qualified electrician if you are not certain of the installation.

CAUTION : Before starting the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

1. Fasten the provided 2 mounting screws to the mounting strap. Make sure the thread of the screw is facing downward when the mounting strap is attached to the outlet box. Fasten the mounting strap using 2 outlet box screws provided.
2. Connect loop of the canopy and loop of the support by using rods as shown.
3. Connect the wire with writing on it from the fixture to the black wire from the supply circuit. Connect the wire without writing on it (with raised ribs) from the fixture to the white wire from the supply circuit. Cover the connections using the wire connectors provided .Tie the ground wires from outlet box and fixture to the ground screw on the mounting strap.
4. Carefully tuck all wiring back into outlet box. Locate the canopy over the outlet box , positioning the mounting screw heads through the holes of canopy. Secure the canopy by using 2 lock nuts provided.
5. Screw the nipple into the bushing of the fixture and fasten it by tightening the hex nut.
6. Install the bulb(bulbs included)
7. Place ceiling pan , glass shade, rubber washer and lock washer over the nipple & secure them using the nut until the glass hold firmly to the fixture ;Place the bottom cap over the nipple and secure it by tightening the finial.